Epson **EB-1940W**

DATASHEET

An ideal device for corporate or educational use, the EB-1940W is a great combination of quality output and features at an affordable price.

KEY FEATURES

- 4,200 lumens White/Colour Light Output
- Can be installed or used portably
- Program projector actions in advance
- Read PDFs directly from a USB stick

Convenient use

The Epson EB-1940W combines high-quality output, value-added features and affordability, into a compact and portable projector. It is perfect for corporate or educational use, as it can be easily installed in meeting rooms or used portably from a desktop.

High quality picture

Utilising Epson's 3LCD technology to ensure clearly projected images, the EB-1940W produces vivid, natural colours and an equally high White and Colour Light Output, even in daylight.

Connectivity

The EB-1940W boasts a DisplayPort connector, allowing you to show high definition audio and video content with ease.

Enhanced productivity

Productivity can be greatly increased with a range of features available with the EB-1940W, such as Quick Corner.

No.1 SINCE 2001
EPSON
WORLD LEADER
IN PROJECTORS
Source: Futuresource Consulting Ltd.

EPSON®
EXCEED YOUR VISION

Epson **EB-1940W**

PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	0,59 inch with MLA (D7)
IMAGE	
Color Light Output	4.200 lumen - 2.910 lumen (economy)
White Light Output	4.200 lumen - 2.910 lumen (economy)
Resolution	WXGA, 1280 x 800, 16:10
Contrast Ratio	3.000 : 1
Lamp	245 W, 2.500 h durability, 4.000 h durability (economy mode)
Keystone Correction	Auto vertical: ± 30 °, Manual horizontal ± 30 °
OPTICAL	
Projection Ratio	1,38 - 2,24:1
Zoom	Manual, Factor: 1, 1,6
Projection Size	29 inches - 280 inches
Projection Distance Wide	0,8 m - 8,4 m
Projection Distance Tele	1,4 m - 13,9 m
Projection Lens F Number	1,51 - 1,99
Focal Distance	18.000 mm - 29.000 mm
Focus	Manual
Offset	10 : 1
CONNECTIVITY	
USB Display Function	3 in 1: Image / Mouse / Sound
Interfaces	USB 2.0 Type B, USB 2.0 Type A, RS-232C, HDMI in, RGB in (2x), RGB out, Stereo mini jack audio out, Stereo mini jack audio in (2x), 10 Base-T, VGA in (2x), VGA out, Composite in, Display Port
Smart device connection	Yes with Epson iOS App
ADVANCED FEATURES	
Security	Kensington lock, Security bar, Control panel lock, Password lock
Features	AV Mute Slide, Automatic input selection, Automatic keystone correction, Direct Power on/off, Document Camera Compatible, Freeze image, Instant on/off, JPEG Viewer, Network administration, PC Free, Quick Corner, Slide show, Split-Screen-Function
Video Color Modes	Blackboard, Dynamic, Photo, Presentation, sRGB, Theatre, Whiteboard, DICOM SIM
GENERAL	
Energy Use	337 W, 250 W (economy), 0,44 W (standby)
Product dimensions	377 x 271 x 108 (Width x Depth x Height)
Product weight	3,7 kg
Noise Level	Normal: 37 dB (A) - Economy: 29 dB (A)
Included Software	EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection, EasyMP Slide Converter
Loudspeaker	10 W

LOGISTICS INFORMATION

SKU	V11H474040
Barcode	8715946512549
Dimensions Single Carton	517 x 342 x 196 mm
Carton Weight	5,51 Kg

WHAT'S IN THE BOX

- Computer cable
- Power cable
- Software (CD)
- User manual
- User manual (CD)
- Remote control incl. batteries

OPTIONAL ACCESSORIES

- Air Filter - ELPAF41 - New EB-19 Series V13H134A41
- Lamp - ELPLP75 - EB-196x/195x/194xW V13H010L75
- Soft Carry Case - ELPKS65 - New EB-19xx V12H001K65
- Ceiling Mount - ELPMB23 - White V12H003B23
- Ceiling pipe - ELPFP13 - 668-918mm V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm V12H003P14

Epson Deutschland GmbH
Otto-Hahn-Str. 4
D-40670 Meerbusch
Info-Line: 01805/23 41 10 (0,14 /Min. aus dem dt. Festnetz, max. 0,42 /Min. aus dem Mobilfunk)
Telefax: +49 (0) 2159/538-3000
www.epson.de

Epson in Österreich
Info-Line: 0810/20 01 13 (0,07 /Min.)
www.epson.at
Epson in der Schweiz
Info-Line: 0848 44 88 20 (8 Rp./Min.)
www.epson.ch

Alle Marken und eingetragenen Warenzeichen sind das Eigentum der Seiko Epson Corporation oder der jeweiligen Rechteinhaber.
Diese Produktinformationen können ohne vorherige Ankündigung geändert werden.